



## SPRINKLER FITTING SYSTEMS

### SERIES AH2-300 BRAIDED FLEXIBLE HOSE

#### PATENTED HOSE TECHNOLOGY

- › highest pressure rating in the industry
- › confidence to go higher and further

#### PROPRIETARY GASKET TECHNOLOGY

- › Victaulic material composition and manufacturing
- › leak-free performance

#### EASE OF INSTALLATION

- › 100% kink resistance
- › strongest braid coverage
- › 90° elbows available for greater installation advantage

#### EASE OF BENDING AND SHAPE RETENTION

- › improved corrugation reduces effort needed to bend hose

#### IMPROVED HYDRAULIC PERFORMANCE

- › up to 50% less friction loss than corrugated systems

#### SINGLE SOURCE CONFIDENCE

- › vertically integrated manufacturing—Victaulic can provide the entire system from the branch fitting to the sprinkler head
- › automated weld technology
- › multi-step automated leak testing

› FLEXIBLE FITTINGS

SUSPENDED CEILING

HARD-LID CEILING

SPECIALTY APPLICATIONS

PRE-ASSEMBLED SYSTEMS



# confidence speed performance

› Rated up to 300psi | 2068 kPa





SPRINKLER FITTING SYSTEMS

Visit [www.victaulic.com/vicflex](http://www.victaulic.com/vicflex) to learn more about the VicFlex system or to request a demo.

## Applications:



### NEW Series AH2-300 Braided Hose

- › FM Approved
- › Rated to 300 psi | 2068 kPa
- › 8" Bend radius
- › Confidence to go higher and further



High-rise buildings



Long horizontal buildings



PB-AH2-300 7720 REV A 10/2013

VICTAULIC AND FIRELOCK ARE REGISTERED TRADEMARKS OF VICTAULIC COMPANY.

VICFLEX IS A TRADEMARK OF VICTAULIC COMPANY. © 2013 VICTAULIC COMPANY. ALL RIGHTS RESERVED.

