


Series 7WX Domestic Water Kit – With TA Series 76X Low Lead Balancing Valve



Kit Size inches DN	Dimensions			End Type	Weight
	A Inches mm	B Inches mm	F Inches mm		Approx. (Each) lb Kg
1/2 DN15	16.75 425	15.20 386	3.07 78	Copper Press Fit	2.5 1.1
1/2 DN15	16.75 425	14.00 356	3.07 78	Sweat	2.4 1.1
3/4 DN20	19.06 484	16.75 425	3.78 96	Copper Press Fit	4.5 2.0
3/4 DN20	19.06 484	16.00 406	3.78 96	Sweat	4.5 2.0

NOTES

- Available flow rates are 0.5, 1 and 2 GPM. Please order the desired flow rate assembly. Contact Victaulic for other needs.
- Copper press fit options are compatible with Viega and Nibco press jaws.
- Victaulic provides loosely threaded-in sweat adapters for installation ease. Solder/braze onto copper pipe prior to applying thread sealant and wrenching into the provided ball valves.



VICTAULIC

VIRTUAL DESIGN AND CONSTRUCTION

NOTE: Contractor to field verify all equipment configurations, nozzle locating dimensions and elevations for conformance to Victaulic layout drawing(s) PRIOR TO CUTTING PIPE. Please notify Victaulic Virtual Design and Construction Division for recommendations regarding any deviations.

All Victaulic drawings and piping engineering submittals will be based on information furnished to us and is provided solely as an aid to procurement and installation. The Victaulic Company is not responsible for design by engineer of record, erection, or operation. Liability of Victaulic Company with reference to descriptions, lengths, locations, dimensions, or any other data shown herein is limited to the amount charged by Victaulic Company for producing the drawing in question. In the event of an order, Victaulic products must be used in accordance with published specifications and Victaulic literature.

Rev	Description	Date

Vic Details : 5773		DRN. BY: NP	
Category: KOIL KIT		DATE: 11/25/2022	
CHK. BY: Checker	DATE:		
7WX Domestic Water Kit – W/ TA Series 76X			REV.