


PRODUCT LEGEND

1	INLET NIPPLE (1" MPT)
2	NUT
3	ADAPTER RING
4	NOT USED
5	STAINLESS STEEL FLEXIBLE UNBRAIDED HOSE (7/8" NOMINAL DIAMETER)
	(LENGTHS AVAILABLE 31" , 36" , 48" , 60" & 72")
6	ADAPTER RING
7	NUT
8	ELBOW REDUCING OUTLET (AVAILABLE 1/2" OR 3/4" FNPT)
9	CENTER BRACKET ASSEMBLY
10	SQUARE BAR (AVAILABLE IN 24" AND 48" LENGTHS)
11	END BRACKET ASSEMBLY
12	SHEET METAL SCREW
13	#8 X 1/2-INCH SELF-TAPPING SCREW
14	VIC MECHANICAL-T OUTLET STYLE 922 FIRELOCK (1" FNPT)
SEE VICTAULIC SUBMITTAL NUMBER 10.89	



NOTES:
1. REFER TO VICTAULIC SUBMITTAL 10.89
FOR ADDITIONAL DETAILS.

UNBRAIDED VICFLEX FLEXIBLE
HOSE SPRINKLER ASSEMBLIES
WITH ELBOW REDUCER
FOR STANDARD PENDENT SPRINKLER



NOTE: Contractor to field verify all equipment configurations, nozzle locating dimensions and elevations for conformance to Victaulic layout drawing(s) PRIOR TO CUTTING PIPE. Please notify Victaulic Virtual Design and Construction Division for recommendations regarding any deviations.

All Victaulic drawings and piping engineering submittals will be based on information furnished to us and is provided solely as an aid to procurement and installation. The Victaulic Company is not responsible for design by engineer of record, erection, or operation. Liability of Victaulic Company with reference to descriptions, lengths, locations, dimensions, or any other data shown herein is limited to the amount charged by Victaulic Company for producing the drawing in question. In the event of an order, Victaulic products must be used in accordance with published specifications and Victaulic literature.

Rev	Description	Date

Vic Details : 0363		DRN. BY: PP	
Category: FP VICFLEX		DATE: 05/28/2020	
CHK. BY: NP	DATE:		
AH5_W_ELBOW_AND_AB7			REV.