


Hard-lid-Ceiling with Recessed Sprinkler



Hose Clearance Chart						
	Straight Reducer				Long Elbow	Short Elbow
	V2707 3/4" Max Recess	V3802 1/2" Max Recess	V2707 3/4" Max Recess	V3802 1/2" Max Recess	V2707 3/4" Max Recess	V3802 1/2" Max Recess
	inches mm	inches mm	inches mm	inches mm	inches mm	inches mm
"R" Minimum Bend Radius	3.0 76		8.0 203	8.0 203	-	
"A" Minimum Required Installation Space	9.8 249	11.2 285	14.8 376	16.2 411	8.0 203	5.9 150

NOTE

Variations of ceiling grids, sprinkler heads, brackets, and hoses are permitted but may result in clearance differences from the figures above.

NOTE: Contractor to find verify all equipment configurations, sizes, and locations. **VERIFY PRIOR TO CUTTING PIPE.** Please refer to Visual Design and Construction Division for recommendations regarding any deviations.

[illegible]

VICTAULIC

Sheet Size: 30" x 42"	DRN. BY: NP	CHK. BY: Checker	
LEVEL:			
HARD-LID-CEILING_ REC_SK_AH2_AB4			
AREA #:			REV.
PROJECT AREA SHEET			