



NOTES-

- 1. ORIENT WITH ONE SET OF DETENT HOLES FACING FORWARD AND THE OTHER SET FACING DOWN AS SHOWN.
- 2. POSITION END BRACKET SUBASSEMBLIES (ITEM 3) AS SHOWN BETWEEN DIMPLES A AND B AND DIMPLES I AND J OF SQUARE BAR (ITEM 1) AND SECURE WITH WING NUT (ITEM 4) TO 25 IN-LBS OF TORQUE.
- 3. ORIENT LABEL (ITEM 5) TO BE READABLE TO AN INSTALLER WORKING FROM BELOW THE CEILING.
- 4. A # 2 SQUARE-RECESSED TOOL INSERT BIT (MCMASTER-CARR #7185A22) IS TO BE PROVIDED IN EVERY BOX OF 5 VB2 BRACKET ASSEMBLIES.
- 5. PACKAGE PER VICTAULIC SPECIFICATION ES1163.



VICTAULIC

VIRTUAL DESIGN AND CONSTRUCTION

NOTE: Contractor to field verify all equipment configurations, nozzle locating dimensions and elevations for conformance to Victaulic layout drawing(s) PRIOR TO CUTTING PIPE. Please notify Victaulic Virtual Design and Construction Division for recommendations regarding any deviations.

All Victaulic drawings and piping engineering submittals will be based on information furnished to us and is provided solely as an aid to procurement and installation. The Victaulic Company is not responsible for design by engineer of record, erection, or operation. Liability of Victaulic Company with reference to descriptions, lengths, locations, dimensions, or any other data shown herein is limited to the amount charged by Victaulic Company for producing the drawing in question. In the event of an order, Victaulic products must be used in accordance with published specifications and Victaulic literature.

Rev	Description	Date

Vic Details : 1026		DRN. BY: PP	
Category: FP SPRINKLER		DATE: 05/28/2020	
CHK. BY: NP	DATE:		
BRACKET ASSEMBLY, T-BAR, FLEX VB2 RECE. PENDENT			REV.